## EMC TEST REPORT

## For

## Hangzhou Meari Technology Co., Ltd.

## **IP** Camera

## Test Model: Bullet 2S

## Additional Model No.: Please Refer To Page 09

Prepared for Address	:	Hangzhou Meari Technology Co., Ltd. No.768 , Jianghong Road,Binjiang, Hangzhou, China
Prepared by Address	:	Shenzhen LCS Compliance Testing Laboratory Ltd. 1/F., Xingyuan Industrial Park, Tongda Road, Bao' an Avenue, Bao' an District, Shenzhen, Guangdong, China
Tel	:	(+86)755-82591330
Fax	:	(+86)755-82591332
Web	:	www.LCS-cert.com
Mail	:	webmaster@LCS-cert.com
Date of receipt of test sample Number of tested samples	:	September 23, 2019
Serial number	:	Prototype
Date of Test	÷	September 23, 2019 ~ September 30, 2019
Date of Report	:	October 17, 2019

# CE

Report No.: LCS190912085AEE001

	EMC TEST REPORT			
Emission standard for Alarm systems - Part 4: Elec requirements for components	<b>N 61000-6-3: 2007+A1: 2011</b> residential, commercial and light-industrial environments <b>EN 50130-4: 2011+A1: 2014</b> ctromagnetic compatibility - Product family standard: Immunity of fire, intruder, hold up, CCTV, access control and social alarm systems			
Report Reference No	: LCS190912085AEE001 : October 17, 2019			
Testing Laboratory Name	: Shenzhen LCS Compliance Testing Laboratory Ltd.			
Address	: 1/F., Xingyuan Industrial Park, Tongda Road, Bao' an Avenue, Bao' an District, Shenzhen, Guangdong, China			
Testing Location/ Procedure	<ul> <li>Full application of Harmonised standards ■</li> <li>Partial application of Harmonised standards □</li> <li>Other standard testing method □</li> </ul>			
Applicant's Name	: Hangzhou Meari Technology Co., Ltd.			
Address	: No.768 , Jianghong Road, Binjiang, Hangzhou, China			
Test Specification Standard	: EN 61000-6-3: 2007+A1: 2011 EN 50130-4: 2011+A1: 2014 EN 61000-3-2: 2014 EN 61000-3-3: 2013			
Test Report Form No	: LCSEMC-1.0			
TRF Originator	Driginator : Shenzhen LCS Compliance Testing Laboratory Ltd.			
Master TRF	: Dated 2011-03			
Shenzhen LCS Compliance To This publication may be reprodu- the Shenzhen LCS Compliance and source of the material. She responsibility for and will not as interpretation of the reproduced	esting Laboratory Ltd. All rights reserved. uced in whole or in part for non-commercial purposes as long a Testing Laboratory Ltd. is acknowledged as copyright owner nzhen LCS Compliance Testing Laboratory Ltd. takes no sume liability for damages resulting from the reader's material due to its placement and context.			
	· IP Camera			
Test Item Description	. IF Califera			
Test Item Description	: N/A			
Test Item Description.         Trade Mark         Test Model	: N/A : Bullet 2S			
Test Item Description Trade Mark Test Model Ratings	<ul> <li>N/A</li> <li>Bullet 2S</li> <li>For: ADAPTER</li> <li>INPUT:100-240V~50/60Hz</li> <li>OUTPUT:12V 1000mA</li> </ul>			
Test Item Description Trade Mark Test Model Ratings Result	<ul> <li>N/A</li> <li>Bullet 2S</li> <li>For: ADAPTER</li> <li>INPUT:100-240V~50/60Hz</li> <li>OUTPUT:12V 1000mA</li> <li>Positive</li> </ul>			
Test Item Description.         Trade Mark         Test Model         Ratings         Result         Compiled by:	<ul> <li>N/A</li> <li>Bullet 2S</li> <li>For: ADAPTER</li> <li>INPUT:100-240V~50/60Hz</li> <li>OUTPUT:12V 1000mA</li> <li>Positive</li> </ul> Supervised by:			
Test Item Description.         Trade Mark         Test Model         Ratings         Result         Compiled by:         Ray Kay	<ul> <li>in California</li> <li>N/A</li> <li>Bullet 2S</li> <li>For: ADAPTER</li> <li>INPUT:100-240V~50/60Hz</li> <li>OUTPUT:12V 1000mA</li> <li>Positive</li> </ul> Supervised by: Aking Jin			

Page 2 of 51

Report No.: LCS190912085AEE001

# **EMC -- TEST REPORT**

Test Report No. :	LCS190912085AEE001
-------------------	--------------------

October 17, 2019

Date of issue

Test Model	: Bullet 2S
EUT	: IP Camera
Applicant	: Hangzhou Meari Technology Co., Ltd.
Address	: No.768 , Jianghong Road,Binjiang, Hangzhou, China
Telephone	:/
Fax	:/
Manufacturer	: Hangzhou Meari Technology Co., Ltd.
Address	: No.768 , Jianghong Road, Binjiang, Hangzhou, China
Address Telephone	: No.768 , Jianghong Road,Binjiang, Hangzhou, China : /
Address Telephone Fax	: No.768 , Jianghong Road,Binjiang, Hangzhou, China : / : /
Address Telephone Fax	: No.768 , Jianghong Road,Binjiang, Hangzhou, China : / : /
Address Telephone Fax	<ul> <li>No.768 , Jianghong Road, Binjiang, Hangzhou, China</li> <li>/</li> <li>/</li> <li>Hangzhou Meari Technology Co., Ltd.</li> </ul>
Address Telephone Fax <b>Factory</b> Address	<ul> <li>No.768 , Jianghong Road, Binjiang, Hangzhou, China</li> <li>/</li> <li>/</li> <li>Hangzhou Meari Technology Co., Ltd.</li> <li>No.768 , Jianghong Road, Binjiang, Hangzhou, China</li> </ul>
Address Telephone Fax <b>Factory</b> Address Telephone	<ul> <li>No.768 , Jianghong Road, Binjiang, Hangzhou, China</li> <li>/</li> <li>/</li> <li>Hangzhou Meari Technology Co., Ltd.</li> <li>No.768 , Jianghong Road, Binjiang, Hangzhou, China</li> <li>/</li> </ul>

## **Test Result**

Positive

The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision	Issue Date	Revisions	Revised By
000	October 17, 2019	Initial Issue	Gavin Liang
001	November 01, 2019	Replaced 48 images	Gavin Liang

# **Revision History**

Note: This report is based on the report No. LCS190912085AEE. This report is replacing the original report

Report No.: LCS190912085AEE001

## TABLE OF CONTENTS

**Test Report Description** 

P	a	g	e
•	u	5	$\mathbf{\tilde{v}}$

1. TEST STANDARDS	6
2.SUMMARY OF STANDARDS AND RESULTS	7
2.1. DESCRIPTION OF STANDARDS AND RESULTS 2.2. DESCRIPTION OF PERFORMANCE CRITERIA	7 8
3. GENERAL INFORMATION	9
<ul> <li>3.1. DESCRIPTION OF DEVICE (EUT)</li></ul>	9 9 9 10
4. MEASURING DEVICES AND TEST EQUIPMENT	11
5. TEST RESULTS	14
<ul> <li>5.1. POWER LINE CONDUCTED EMISSION MEASUREMENT.</li> <li>5.2. RADIATED EMISSION MEASUREMENT.</li> <li>5.3. HARMONIC CURRENT EMISSION MEASUREMENT.</li> <li>5.4. VOLTAGE FLUCTUATION AND FLICKER MEASUREMENT.</li> <li>5.5. ELECTROSTATIC DISCHARGE IMMUNITY TEST.</li> <li>5.6. RF FIELD STRENGTH SUSCEPTIBILITY TEST.</li> <li>5.7. ELECTRICAL FAST TRANSIENT/BURST IMMUNITY TEST.</li> </ul>	14 20 21 22 25 29
5.8. SURGE IMMUNITY TEST 5.9. INJECTED CURRENTS SUSCEPTIBILITY TEST 5.10. VOLTAGE DIPS AND INTERRUPTIONS TEST	32 35 38
5.8. SURGE IMMUNITY TEST 5.9. INJECTED CURRENTS SUSCEPTIBILITY TEST 5.10. VOLTAGE DIPS AND INTERRUPTIONS TEST 6. PHOTOGRAPHS OF TEST SETUP	32 35 38 40

## 1. TEST STANDARDS

## The tests were performed according to following standards:

EN 61000-6-3: 2007+A1: 2011 Emission standard for residential, commercial and light-industrial environments

<u>EN 50130-4: 2011+A1: 2014</u> Alarm systems - Part 4: Electromagnetic compatibility - Product family standard: Immunity requirements for components of fire, intruder, hold up, CCTV, access control and social alarm systems

<u>EN 61000-3-2: 2014</u> Electromagnetic compatibility (EMC) -- Part 3-2: Limits - Limits for harmonic current emissions (equipment input current up to and including 16 A per phase) <u>EN 61000-3-3: 2013</u> Electromagnetic compatibility (EMC) -- Part 3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current  $\leq$  16 A per phase and not subject to conditional connection

## 2.SUMMARY OF STANDARDS AND RESULTS

#### 2.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

Emission (EN 61000-6-3: 2007+A1: 2011)					
Description of Test Item	Standard	Limits	Results		
Conducted disturbance at mains terminals	EN 55032: 2015	Class B	PASS		
Conducted disturbance at telecommunication port	EN 55032: 2015	Class B	N/A		
Radiated disturbance	EN 55032: 2015	Class B	PASS		
Harmonic current emissions	EN 61000-3-2: 2014	Class A	PASS		
Voltage fluctuations & flicker	EN 61000-3-3: 2013		PASS		
Im	munity (EN 50130-4: 2011+A1	: 2014)			
Description of Test Item	Basic Standard	Performance Criteria	Results		
Electrostatic discharge (ESD)	EN 61000-4-2: 2009	В	PASS		
Radio-frequency, Continuous radiated disturbance	EN 61000-4-3: 2006+A2: 2010	А	PASS		
Electrical fast transient (EFT)	EN 61000-4-4: 2012	В	PASS		
Surge (Input a.c. power ports)	EN 61000 4 5: 2014, 41: 2017	В	PASS		
Surge (Telecommunication ports)	EN 01000-4-5. 2014+A1. 2017	В	N/A		
Radio-frequency, Continuous conducted disturbance	EN 61000-4-6: 2014	А	PASS		
Power frequency magnetic field	EN 61000-4-8: 2010	А	N/A		
Voltage dips, >95% reduction		В	PASS		
Voltage dips, 30% reduction	EN 61000-4-11: 2004+A1: 2017	С	PASS		
Voltage interruptions		С	PASS		
***Note: N/A is an abbreviation for Not Applicable.					

Test mode:				
Mode 1	Full Load	Record		
Mode 2	No Load	Pre-scan		
Mode 3	Half Load	Pre-scan		
***Note: All test modes were tested, but we only recorded the worst case in this report.				

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 7 of 51

## 2.2. Description of Performance Criteria

#### General Performance Criteria

Examples of functions defined by the manufacturer to be evaluated during testing include, but are not limited to, the following:

- essential operational modes and states;

tests of all peripheral access (hard disks, floppy disks, printers, keyboard, mouse, etc.);

- quality of software execution;
- quality of data display and transmission;
- quality of speech transmission.

#### 2.2.1. Performance criterion A

The equipment shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed below a performance level specified by the manufacture when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be deriver from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.

#### 2.2.2. Performance criterion B

After the test, the equipment shall continue to operate as intended without operator intervention. No degradation of performance or loss of function is allowed, after the application of the phenomena below a performance level specified by the manufacture, when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance.

During the test, degradation of performance is allowed. However, no change of operation state or stored data is allowed to persist after the test.

If the minimum performance level (or the permissible performance loss) is not specified by the manufacturer, then either of these may be deriver from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.

#### 2.2.3. Performance criterion C

Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacture's instructions.

Functions, and/or information stored in non-volatile memory, or protected by a battery backup, shall not be loss.

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 8 of 51

#### Report No.: LCS190912085AEE001

## **3. GENERAL INFORMATION**

#### 3.1. Description of Device (EUT)

EUT	: IP Camera
Trade Mark	: N/A
Test Model	: Bullet 2S
Additional Model	: Bullet 2X, IPCAM-FE02, NX-4547-675
Model Declaration	$_{\rm 2}$ only for the annex models, with same sockets in minor difference, as color and appearance, less than 20 models in total
Power Supply	. For: ADAPTER INPUT:100-240V~50/60Hz OUTPUT:12V=== 1000mA

EUT Clock Frequency :  $\leq 108$ MHz

#### 3.2. Description of Test Facility

FCC Registration Number is 254912. Industry Canada Registration Number is 9642A-1. ESMD Registration Number is ARCB0108. UL Registration Number is 100571-492. TUV SUD Registration Number is SCN1081. TUV RH Registration Number is UA 50296516-001 NVLAP Registration Code is 600167-0.

#### 3.3. Statement of The Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 9 of 51

Test	Parameters	Expanded uncertainty (U <sub>lab</sub> )	Expanded uncertainty (U <sub>cispr</sub> )
Conducted Emission	Level accuracy (9kHz to 150kHz) (150kHz to 30MHz)	± 2.63 dB ± 2.35 dB	± 3.8 dB ± 3.4 dB
Power disturbance	Level accuracy (30MHz to 300MHz)	$\pm$ 2.90dB	$\pm$ 4.5 dB
Electromagnetic Radiated Emission (3-loop)	Level accuracy (9kHz to 30MHz)	$\pm$ 3.60 dB	± 3.3 dB
Radiated Emission	Level accuracy (9kHz to 30MHz)	$\pm$ 3.68 dB	N/A
Radiated Emission	Level accuracy (30MHz to 1000MHz)	$\pm$ 3.48 dB	$\pm$ 5.3 dB
Radiated Emission	Level accuracy (above 1000MHz)	$\pm$ 3.90 dB	$\pm$ 5.2 dB
Mains Harmonic	Voltage	± 0.510%	N/A
Voltage Fluctuations & Flicker	Voltage	± 0.510%	N/A
EMF	/	± 21.59%	N/A

#### 3.4. Measurement Uncertainty

1) Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus.

2) The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

## **4. MEASURING DEVICES AND TEST EQUIPMENT**

Test Item: Conducted Disturbance						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	
1	EMI Test Software	AUDIX	E3	/	N/A	
2	EMI Test Receiver	R&S	ESPI	101840	2019-06-11	
3	Artificial Mains	R&S	ENV216	101288	2019-06-12	
4	10dB Attenuator	SCHWARZBECK	MTS-IMP-136	261115-001-0032	2019-06-11	
5	Impedance Stabilization Network	TESEQ	ISN T800	45130	2018-11-15	

## Test Item: Radiated Disturbance (Electric Field)

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI Test Software	AUDIX	E3	/	N/A
2	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2019-06-12
3	Positioning Controller	MF	MF-7082	/	2019-06-12
4	By-log Antenna	SCHWARZBECK	VULB9163	9163-470	2019-07-25
5	Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1925	2019-07-01
6	EMI Test Receiver	R&S	ESR 7	101181	2019-06-12
7	RS SPECTRUM ANALYZER	R&S	FSP40	100503	2018-11-15
8	Broadband Preamplifier	/	BP-01M18G	P190501	2019-07-01
9	RF Cable-R03m	Jye Bao	RG142	CB021	2019-06-12
10	RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	2019-06-12

## **Test Item: Harmonic Current**

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	Power Analyzer Test System	Voltech	PM6000	20000670053	2019-06-12

Test Item: Voltage fluctuation and Flicker						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	
1	Power Analyzer Test System	Voltech	PM6000	20000670053	2019-06-12	

Test Item: Electrostatic Discharge						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	
1	ESD Simulator	SCHLODER	SESD 230	604035	2019-06-13	

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 11 of 51

Report No.: LCS190912085AEE001

Tes	Test Item: RF Field Strength Susceptibility						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.		
1	RS Test Software	Tonscend	/	/	N/A		
2	ESG Vector Signal Generator	Agilent	E4438C	MY42081396	2018-11-15		
3	3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	2019-06-12		
4	RF POWER AMPLIFIER	OPHIR	5225R	1052	NCR		
5	RF POWER AMPLIFIER	OPHIR	5273F	1019	NCR		
6	Stacked Broadband Log Periodic Antenna	SCHWARZBECK	STLP 9128	9128ES-145	NCR		
7	Stacked Mikrowellen LogPer Antenna	SCHWARZBECK	STLP 9149	9149-484	NCR		
8	Electric field probe	Narda S.TS./PMM	EP601	611WX80208	2019-03-25		
Note: NCR means no calibration requirement							

## **Test Item: Electrical Fast Transient/Burst**

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	Immunity Simulative Generator	EM TEST	UCS500 M4	0101-34	2019-06-11

Test Item: Surge						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	
1	Immunity Simulative Generator	EM TEST	UCS500 M4	0101-34	2019-06-11	

Test Item: Conducted Susceptibility						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	
1	Simulator	FRANKONIA	CIT-10/75	A126A1195	2019-06-11	
2	CDN	FRANKONIA	CDN-M2+M3	A2210177	2019-06-11	
3	6dB Attenuator	FRANKONIA	DAM25W	1172040	2019-06-11	

Test Item: Power Frequency Magnetic Field Susceptibility						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	
1	Power frequency mag-field generator System	EVERFINE	EMS61000-8K	906003	2019-06-11	

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 12 of 51

Г

Report No.: LCS190912085AEE001

Test Item: Voltage Dips						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	
1	Voltage dips and up generator	3CTEST	VDG-1105G	EC0171014	2019-06-11	

Test Item: Voltage Short Interruptions						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	
1	Voltage dips and up generator	3CTEST	VDG-1105G	EC0171014	2019-06-11	

## 5. TEST RESULTS

## 5.1. POWER LINE CONDUCTED EMISSION MEASUREMENT

## 5.1.1. Block Diagram of Test Setup



## 5.1.2. Test Standard

EN 61000-6-3: 2007+A1: 2011 (EN 55032: 2015)

Power Line Conducted Emission Limits (Class B)					
Frequency	Limit (	dBμV)			
(MHz)	Quasi-peak Level	Average Level			
0.15 ~ 0.50	66.0 ~ 56.0 *	56.0 ~ 46.0 *			
0.50 ~ 5.00	56.0	46.0			
5.00 ~ 30.00	60.0	50.0			
NOTE1-The lower limit shall apply at the transition frequencies.					

NOTE2-The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

## 5.1.3. EUT Configuration on Test

The following equipments are installed on Power Line Conducted Emission Measurement to meet the EN 55032 requirement and operating regulations in a manner, which tends to maximize its emission characteristics in a normal application.

## 5.1.4. Operating Condition of EUT

- 5.1.4.1.Setup the EUT as shown on Section 5.1.1
- 5.1.4.2. Turn on the power of all equipments.
- 5.1.4.3.Let the EUT work in measuring Mode 1 and measure it.

## 5.1.5. Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and connected to the AC mains through Line Impedance Stability Network (L.I.S.N). This provided 50-ohm coupling impedance for the tested equipments. Both sides of AC line are investigated to find out the maximum conducted emission according to the EN 55032 regulations during conducted emission measurement.

The bandwidth of the field strength meter is set at 9kHz in 150kHz~30MHz. The frequency range from 150kHz to 30MHz is investigated.

## 5.1.6. Test Results

## PASS.

The test result please refer to the next page.

Report No.: LCS190912085AEE001





Note: Pre-Scan all mode, Thus record worse case mode result in this report.

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 16 of 51

#### 5.2. RADIATED EMISSION MEASUREMENT

## 5.2.1. Block Diagram of Test Setup



Below 1GHz



Above 1GHz

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 17 of 51

## 5.2.2. Test Standard

EN 61000-6-3: 2007+A1: 2011 (EN 55032: 2015) Class B

All emanations from a class B device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified below:

Limits for Radiated Emission Below 1GHz							
Frequency (MHz)	Distance (Meters)	Field Strengths Limit (dBµV/m)					
30 ~ 230	3	40					
230 ~ 1000	3	47					

#### \*\*\*Note:

(1) The smaller limit shall apply at the combination point between two frequency bands.
(2) Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the EUT.

Limits for Radiated Emission Above 1GHz						
Frequency	Distance	Peak Limit	Average Limit			
(MHz)	(Meters)	(dBµV/m)	(dBµV/m)			
1000 ~ 3000	3	70	50			
3000 ~ 6000 3 74 54						
***Note: The lower limit applies at the transition frequency.						

## 5.2.3. EUT Configuration on Test

The EN 55032 regulations test method must be used to find the maximum emission during radiated emission measurement.

## 5.2.4. Operating Condition of EUT

5.2.4.1.Turn on the power.

5.2.4.2.Let the EUT work in the test Mode 1 and measure it.

#### 5.2.5. Test Procedure

The EUT is placed on a turntable, which is 0.8 meter high above the ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. By-log antenna is used as a receiving antenna. Both horizontal and vertical polarization of the antenna is set on test.

The bandwidth of the EMI test receiver is set at RBW/VBW=120kHz/300kHz.

The frequency range from 30MHz to 1000MHz is checked.

The bandwidth of the Spectrum analyzer is set at RBW/VBW=1MHz/3MHz.

The frequency range from 1GHz to the frequency which about 5th carrier harmonic or 6GHz is checked.

## 5.2.6. Test Results

## PASS.

The test result please refer to the next page.

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 18 of 51



This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 19 of 51

## 5.3. HARMONIC CURRENT EMISSION MEASUREMENT

## 5.3.1. Block Diagram of Test Setup



## 5.3.2. Test Standard

EN 61000-3-2: 2014

## 5.3.3. Operating Condition of EUT

Same as Section 5.2.4, except the test setup replaced as Section 5.3.1.

## 5.3.4. Test Results

## Pass

Because the power of EUT is less than 75W, according to standard EN 61000-3-2, harmonic current is unnecessary to test.

## 5.4. VOLTAGE FLUCTUATION AND FLICKER MEASUREMENT

## 5.4.1. Block Diagram of Test Setup



#### 5.4.2. Test Standard

EN 61000-3-3: 2013

## 5.4.3. Operating Condition of EUT

Same as Section 5.2.4, except the test setup replaced as Section 5.4.1.

#### 5.4.4. Test Results

PASS.

Test Model		Bullet 2S		Test Engineer	QU	XIN
Test Voltage		AC 230V/50Hz				
Overall Result:	Note	s:				
	Meas	surement method	- Voltage			
PASS						
I						
		Pst	dc (%)	dmax (%)		Tmax(> 3.3%)(ms)
Limit		1.000	3.300	4.000		500
Reading 1		0.090	0.006	0.240		0

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 21 of 51

## 5.5. ELECTROSTATIC DISCHARGE IMMUNITY TEST

#### 5.5.1. Block Diagram of Test Setup



#### 5.5.2. Test Standard

~ 4 ~

EN 50130-4: 2011+A1: 2014 (EN 61000-4-2: 2009, Severity Level: 3 / Air Discharge:  $\pm$  8KV, Level: 3 / Contact Discharge:  $\pm$  6KV)

#### 5.5.3. Severity Levels and Performance Criterion

5.5.3.1. Severity level		
Level	Test Voltage Contact Discharge (KV)	Test Voltage Air Discharge (KV)
1	±2	±2
2	±4	±4
3	±6	±8
4	±8	±15
X	Special	Special

5.5.3.2. Performance Criterion Performance Criterion: B

## 5.5.4. EUT Configuration on Test

The configuration of EUT is listed in Section 4.

#### 5.5.5. Operating Condition of EUT

Same as conducted emission measurement, which is listed in Section 5.1.4. Except the test set up replaced by Section 5.5.1.

## 5.5.6. Test Procedure

## 5.5.6.1. Air Discharge

This test is done on a non-conductive surface. The round discharge tip of the discharge electrode shall be approached as fast as possible to touch the EUT. After each discharge, the discharge electrode shall be removed from the EUT. The generator is then re-triggered for a new single discharge and repeated 10 times for each pre-selected test point. This procedure shall be repeated until all the air discharge completed

## 5.5.6.2. Contact Discharge

All the procedure shall be same as Section 5.5.6.1. Except that the tip of the discharge electrode shall touch the EUT before the discharge switch is operated.

## 5.5.6.3. Indirect Discharge For Horizontal Coupling Plane

At least 10 single discharges (in the most sensitive polarity) shall be applied at the front edge of each HCP opposite the center point of each unit (if applicable) of the EUT and 0.1m from the front of the EUT. The long axis of the discharge electrode shall be in the plane of the HCP and perpendicular to its front edge during the discharge.

## 5.5.6.4. Indirect Discharge For Vertical Coupling Plane

At least 10 single discharge (in the most sensitive polarity) shall be applied to the center of one vertical edge of the coupling plane. The coupling plane, of dimensions 0.5m X 0.5m, is placed parallel to, and positioned at a distance of 0.1m from the EUT. Discharges shall be applied to the coupling plane, with this plane in sufficient different positions that the four faces of the EUT are completely illuminated.

## 5.5.7. Test Results

## PASS.

The test result please refer to the next page.

Report No.: LCS190912085AEE001

Electrostatic Discharge Test Results					
Standard	□ IEC 61000-4-2 ☑ EN 61000-4-2				
Applicant	Hangzhou Meari Technology Co., Ltd.				
EUT	IP Camera	Temperature	<b>23.7</b> ℃		
M/N	Bullet 2S	Humidity	52.6%		
Criterion	В	Pressure	1021mbar		
Test Mode	Mode 1	Test Engineer	QUXIN		
Test Voltage	AC 230V/50Hz	Test voltage	AC 230V/50Hz		

Air Discharge								
		<b>Test Levels</b>			Result	S		
Test Points	± 2kV	± 4kV	± 8kV	Passed	Fail	Performance Criterion		
Front	$\boxtimes$	$\square$	$\square$	$\square$		□A ⊠B		
Back	$\boxtimes$	$\square$	$\boxtimes$	$\square$		□A ⊠B		
Left	$\boxtimes$	$\square$	$\boxtimes$	$\boxtimes$		□A ⊠B		
Right	$\boxtimes$	$\square$	$\square$	$\boxtimes$		□A ⊠B		
Тор	$\boxtimes$	$\square$	$\square$	$\boxtimes$		□A ⊠B		
Bottom	$\boxtimes$	$\square$	$\square$	$\square$		□A ⊠B		
	Contact Discharge							

|--|

	Test L		Results			
Test Points	± 2 kV	±4 kV	± 6 kV	Passed	Fail	Performance Criterion
Front	$\square$	$\square$	$\square$	$\square$		□A ⊠B
Back	$\square$	$\square$	$\square$	$\square$		□A ⊠B
Left	$\square$	$\square$	$\square$	$\square$		□A ⊠B
Right	$\square$	$\square$	$\square$	$\square$		□A ⊠B
Тор	$\square$	$\square$	$\square$			□A ⊠B
Bottom	$\square$	$\square$	$\square$			

Discharge	To H	Iorizontal	Cou	pling	Plane

	Test L	Results					
Side of EUT	± 2 kV	± 4 kV	± 6 kV	Passed	Fail	Perfor Crite	mance erion
Front	$\square$	$\square$	$\boxtimes$	$\boxtimes$		ΠA	ØВ
Back	$\square$	$\square$	$\boxtimes$	$\boxtimes$		ΠA	⊠Β
Left	$\square$	$\square$	$\boxtimes$	$\boxtimes$		ΠA	⊠В
Right	$\square$	$\square$	$\boxtimes$	$\boxtimes$		A	⊠B
	- · · ·						

#### **Discharge To Vertical Coupling Plane**

	Test I		Results			
Side of EUT	± 2 kV	±4 kV	± 6 kV	Passed	Fail	Performance Criterion
Front	$\boxtimes$	$\square$	$\boxtimes$	$\boxtimes$		□A ⊠B
Back	$\boxtimes$	$\square$	$\boxtimes$	$\boxtimes$		□A ⊠B
Left	$\boxtimes$	$\square$	$\boxtimes$	$\boxtimes$		□A ⊠B
Right	$\boxtimes$	$\square$	$\boxtimes$	$\boxtimes$		□A ⊠B

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 24 of 51

## 5.6. RF FIELD STRENGTH SUSCEPTIBILITY TEST

## 5.6.1. Block Diagram of Test Setup



This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 25 of 51

#### 5.6.2. Test Standard

## EN 50130-4: 2011+A1: 2014 (EN 61000-4-3: 2006+A2: 2010 Severity Level 3: 10V / m)

#### 5.6.3. Severity Levels and Performance Criterion

5.6.3.1.	Severity	level
----------	----------	-------

Level	Field Strength (V/m)
1	1
2	3
3	10
Х	1

5.6.3.2. Performance Criterion Performance Criterion: A

#### 5.6.4. EUT Configuration on Test

The configuration of EUT is listed in Section 4

#### 5.6.5. Operating Condition of EUT

Same as radiated emission measurement, which is listed in Section 5.2.4, except the test setup replaced as Section 5.6.1.

\_\_\_\_\_

## 5.6.6. Test Procedure

The EUT are placed on a table, which is 0.8 meter high above the ground. The EUT is set 3 meters away from the transmitting antenna, which is mounted on an antenna tower. Both horizontal and vertical polarization of the antenna is set on test. Each of the four sides of the EUT must be faced this transmitting antenna and measured individually. In order to judge the EUT performance, a CCD Recording is used to monitor its screen. All the scanning conditions are as following:

Condition of Test

-----

Remark

- 1. Fielded Strength
- 2. Radiated Signal
- 3. Scanning Frequency
- 4. Sweep Time of Radiated
- 5. Dwell Time

## 5.6.7. Test Results

PASS.

The test result please refer to the next page.

10V/m (Severity Level 3) Unmodulated 80-200MHz 0.0015 Decade/s 3 Sec.

Report No.: LCS190912085AEE001

RF Field Strength Susceptibility Test Results				
Standard	□ IEC 61000-4-3  ☑ EN 61000-4-3			
Applicant	Hangzhou Meari Technology Co., Ltd.			
EUT	IP Camera	Temperature	<b>24.7</b> ℃	
M/N	Bullet 2S	Humidity	53.7%	
Test Mode	Mode 1	Criterion	A	
Field Strength	10 V/m	Frequency Range	80 MHz to200MHz	
Test Engineer	QUXIN	Test Voltage	AC 230V/50Hz	
Modulation	□None □ Pulse	☑AM 1KHz 809	%	
Steps	1%			

	Horizontal	Vertical
Front	PASS	PASS
Right	PASS	PASS
Rear	PASS	PASS
Left	PASS	PASS

Note:

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 28 of 51

## 5.7. ELECTRICAL FAST TRANSIENT/BURST IMMUNITY TEST

## 5.7.1. Block Diagram of Test Setup



## 5.7.2. Test Standard

EN 50130-4: 2011+A1: 2014 (EN 61000-4-4: 2012, Severity Level, Level 3: 2KV)

## 5.7.3. Severity Levels and Performance Criterion

Open Circuit Output Test Voltage ±10%			
Level	On Power Supply Lines	On I/O (Input/Output) Signal	
		data and control lines	
1	0.5 KV	0.25 KV	
2	1 KV	0.5 KV	
3	2 KV	1 KV	
4	4 KV	2 KV	
Х	Special	Special	

5.7.3.2. Performance Criterion

Performance Criterion: B

## 5.7.4. EUT Configuration on Test

The configuration of EUT is listed in Section 4

## 5.7.5. Operating Condition of EUT

- 5.7.5.1. Setup the EUT as shown in Section 5.7.1.
- 5.7.5.2. Turn on the power of all equipments.
- 5.7.5.3. Let the EUT work in test Mode 1 and measure it.

## 5.7.6. Test Procedure

The EUT is put on the table, which is 0.8 meter high above the ground. This reference ground plane shall project beyond the EUT by at least 0.1m on all sides and the minimum distance between EUT and all other conductive structure, except the ground plane beneath the EUT, shall be more than 0.5m.

5.7.6.1. For input and output AC power ports:

The EUT is connected to the power mains by using a coupling device, which couples the EFT interference signal to AC power lines. Both polarities of the test voltage should be applied during compliance test and the duration of the test is 1 mins.

5.7.6.2. For signal lines and control lines ports: It's unnecessary to test.

5.7.6.3. For DC output line ports: It's unnecessary to test.

## 5.7.7. Test Results

## PASS.

The test result please refer to the next page.

Report No.: LCS190912085AEE001

Electrical Fast Transient/Burst Test Results			
Standard	□ IEC 61000-4-4 ☑ EN 61000-4-4		
Applicant	Hangzhou Meari Technology Co., Ltd.		
EUT	IP Camera	Temperature	<b>24.6</b> ℃
M/N	Bullet 2S	Humidity	53.7%
Test Mode	Mode 1	Criterion	В
Test Engineer	QUXIN	Test Voltage	AC 230V/50Hz

Line	Test Voltage	Result (+)	Result (-)
L	2KV	PASS	PASS
N	2KV	PASS	PASS
PE			
L-N	2KV	PASS	PASS
L-PE			
N-PE			
L-N-PE			
Signal Line			
I/O Cable			

Note:

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 31 of 51

Report No.: LCS190912085AEE001

#### 5.8. SURGE IMMUNITY TEST

#### 5.8.1. Block Diagram of Test Setup



#### 5.8.2. Test Standard

EN 50130-4: 2011+A1: 2014 (EN 61000-4-5: 2014+A1: 2017, Severity Level: Line to Line: Level 2, 1.0KV, Line to Earth: Level 3, 2.0KV)

#### 5.8.3. Severity Levels and Performance Criterion

Severity Level	Open-Circuit Test Voltage (KV)
1	0.5
2	1.0
3	2.0
4	4.0
*	Special

5.8.3.2. Performance Criterion Performance Criterion: B

#### 5.8.4. EUT Configuration on Test

The configuration of EUT is listed in Section 4

#### 5.8.5. Operating Condition of EUT

- 5.8.5.1.Setup the EUT as shown in Section 5.8.1.
- 5.8.5.1.Turn on the power of all equipments.
- 5.8.5.1.Let the EUT work in test mode and measure it.

## 5.8.6. Test Procedure

5.8.6.1. Set up the EUT and test generator as shown on Section 5.8.1.

5.8.6.2. For line to line coupling mode, provide a 1.0 KV 1.2/50us voltage surge (at open-circuit condition) and 8/20us current surge to EUT selected points.

5.8.6.3. At least 5 positive and 5 negative (polarity) tests with a maximum 1/min repetition rate are conducted during test.

5.8.6.4. Different phase angles are done individually.

5.8.6.5. Record the EUT operating situation during compliance test and decide the EUT immunity criterion for above each test.

## 5.8.7. Test Results

#### PASS.

The test result please refer to the next page.

Report No.: LCS190912085AEE001

Surge Immunity Test Result			
Standard	□ IEC 61000-4-5  ☑ EN 61000-4-5		
Applicant	Hangzhou Meari Technology Co., Ltd.		
EUT	IP Camera	Temperature	<b>24.7</b> ℃
M/N	Bullet 2S	Humidity	54.5%
Test Mode	Mode 1	Criterion	В
Test Engineer	QUXIN	Test Voltage	AC 230V/50Hz

Location	Polarity	Phase Angle	nase Number Pulse Voltage ngle of Pulse (KV)			
L-N	+	0°, 90°, 180°, 270°	5	1.0	PASS	
	-	0°, 90°, 180°, 270°	5	1.0	PASS	
L-PE						
N-PE						
Signal Line						
Note						

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 34 of 51

## 5.9. INJECTED CURRENTS SUSCEPTIBILITY TEST

#### 5.9.1. Block Diagram of Test Setup



#### 5.9.2. Test Standard

EN 50130-4: 2011+A1: 2014(EN 61000-4-6: 2014, Severity Level: Level 3, 10V (rms), (0.15MHz ~ 100MHz))

#### 5.9.3. Severity Levels and Performance Criterion

5.9	9.3	1.	Severity	level
-----	-----	----	----------	-------

Level	Field Strength (V)		
1	1		
2	3		
3	10		
Х	Special		

5.9.3.2. Performance Criterion Performance Criterion: A

#### 5.9.4. EUT Configuration on Test

The configuration of EUT is listed in Section 4

#### 5.9.5. Operating Condition of EUT

- 5.9.5.1. Setup the EUT as shown in Section 5.9.1.
- 5.9.5.2. Turn on the power of all equipments.
- 5.9.5.3.Let the EUT work in test Mode 1 and measure it.

#### 5.9.6. Test Procedure

5.9.6.1. Set up the EUT, CDN and test generators as shown on Section 5.9.1.

5.9.6.2. Let the EUT work in test mode and measure it.

5.9.6.3. The EUT are placed on an insulating support 0.1m high above a ground reference plane. CDN (coupling and decoupling device) is placed on the ground plane about 0.3m from EUT. Cables between CDN and EUT are as short as possible, and their height above the ground reference plane shall be between 30 and 50 mm (where possible).

5.9.6.4. The disturbance signal described below is injected to EUT through CDN. 5.9.6.5. The EUT operates within its operational mode(s) under intended climatic conditions after power on.

5.9.6.6. The frequency range is swept from 150kHz to 10MHz using 3V signal level,10MHz to 30MHz using 3V to 1V signal level,30MHz to 80MHz using 1V signal level, and with the disturbance signal 80% amplitude modulated with a 1kHz sine wave. 5.9.6.7. The rate of sweep shall not exceed 1.5\*10-3decades/s. where the frequency is swept incrementally; the step size shall not exceed 1% of the start and thereafter 1% of the preceding frequency value.

5.9.6.8. Recording the EUT operating situation during compliance testing and decide the EUT immunity criterion.

## 5.9.7. Test Results

## PASS.

The test result please refer to the next page.

Report No.: LCS190912085AEE001

Injected Currents Susceptibility Test Results					
Standard	□ IEC 61000-4-6   ☑ EN 61000-4-6				
Applicant	Hangzhou Meari Technology Co., Ltd.				
EUT	IP Camera	Temperature	<b>25.1</b> ℃		
M/N	Bullet 2S	Humidity	54.1%		
Test Mode	Mode 1	Criterion	А		
Test Engineer	QUXIN	Test Voltage	AC 230V/50Hz		

Frequency Range (MHz)	Injected Position	Strength (Unmodulated)	Criterion	Result		
0.15 ~ 100	AC Mains	10V	А	PASS		
Remark:		· · · · · · · · · · · · · · · · · · ·				
1. Modulation Signal:1kHz 80% AM						
2. Measurement Equipment :						
Simulator: CIT-10 (FRANKONIA)						
CDN : 🗹 CDN-M2 (FRANKONIA)						
CDN-M3 (FRANKONIA)						
Note:						

Report No.: LCS190912085AEE001

## 5.10. VOLTAGE DIPS AND INTERRUPTIONS TEST

## 5.10.1. Block Diagram of Test Setup



#### 5.10.2. Test Standard

EN 50130-4: 2011+A1: 2014 (EN 61000-4-11: 2004+A1: 2017)

#### 5.10.3. Severity Levels and Performance Criterion

5.	1	0.3.	1.	Severitv	level
۰.	•	0.0.		0010111	

Test Level (%UT)	Voltage dip and short interruptions (%UT)	Duration (in period)
70	30	0,5; 1; 5 and 10
40	60	0,5; 1; 5 and 10
0	100	0.5, 1 and 5

5.10.3.2. Performance Criterion Performance Criterion: B&C

## 5.10.4. EUT Configuration on Test

The configuration of EUT is listed in Section 4

## 5.10.5. Operating Condition of EUT

- 5.10.5.1. Setup the EUT as shown in Section 5.10.1.
- 5.10.5.2. Turn on the power of all equipments.
- 5.10.5.3. Let the EUT work in test mode and measure it.

## 5.11.6. Test Procedure

5.10.6.1. Set up the EUT and test generator as shown on Section 5.10.1.

5.10.6.2. The interruptions are introduced at selected phase angles with specified duration.

5.10.6.3. Record any degradation of performance.

## 5.10.7. Test Results

## PASS.

The test result please refer to the next page.

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 38 of 51

Report No.: LCS190912085AEE001

Voltage Dips And Interruptions Test Results					
Standard	□ IEC 61000-4-11   ☑ EN 61000-4-11				
Applicant	Hangzhou Meari Technology Co., Ltd.				
EUT	IP Camera	Temperature	<b>24.3</b> ℃		
M/N	Bullet 2S	Humidity	53.2%		
Test Mode	Mode 1	Criterion	B&C		
Test Engineer	QUXIN	Test Voltage	AC 230V/50Hz		

Test Level % U⊤	Voltage Dips & Short Interruptions % U <sub>T</sub>	Duration (in periods)	Criterion	Result
70	30	0P, 1P, 5P, 10P	В	PASS
40	60	0.5P, 1P, 5P, 10P	С	PASS
0	100	0.5P, 1P, 5P	С	PASS

Note:

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 39 of 51

## 6. PHOTOGRAPHS OF TEST SETUP



Test Setup Photo of Power Line Conducted Measurement



Test Setup Photo of Radiated Measurement (30MHz~1GHz)

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 40 of 51

Report No.: LCS190912085AEE001



Test Setup Photo of Harmonic & Flicker Measurement



Test Setup Photo of Electrostatic Discharge Test

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 41 of 51



Test Setup Photo of RF Electromagnetic Field Measurement



Photo of Electrical Fast Transient/Burst Test & Surge Immunity Test

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 42 of 51



Test Setup Photo of Injected Currents Susceptibility Test



Test Setup Photo of Voltage Dips and Interruptions Test

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 43 of 51

## 7. PHOTOGRAPHS OF THE EUT



Fig. 1



Fig. 2

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 44 of 51



Fig. 3



Fig. 4

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 45 of 51

Report No.: LCS190912085AEE001



Fig. 5



Fig. 6

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 46 of 51

Report No.: LCS190912085AEE001



Fig. 7



Fig. 8

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 47 of 51



Fig. 9



Fig. 10

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 48 of 51



Fig. 11



Fig. 12

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 49 of 51



Fig. 13



Fig. 14

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 50 of 51



Fig. 15



Fig. 16

## ----- THE END OF TEST REPORT ------

This report shall not be reproduced except in full, without the written approval of Shenzhen LCS Compliance Testing Laboratory Ltd. Page 51 of 51